

# Kybernetika

VOLUME 38 (2002), NUMBER 5

The Journal of the Czech Society for  
Cybernetics and Information Sciences

Published by:

Institute of Information Theory  
and Automation of the Academy  
of Sciences of the Czech Republic

Editor-in-Chief:

Milan Mareš

Managing Editors:

Karel Sladký

Editorial Board:

Jiří Anděl, Marie Demlová, Petr Hájek,  
Martin Janžura, Jan Ježek, Radim Jiroušek,  
George Klir, Ivan Kramosil, Friedrich Liese,  
Jean-Jacques Loiseau, František Matúš,  
Radko Mesiar, Jiří Outrata, Jan Štecha,  
Olga Štěpánková, Igor Vajda, Pavel Zítek,  
Pavel Žampa

Editorial Office:

Pod Vodárenskou věží 4, 182 08 Praha 8

*Kybernetika* is a bi-monthly international journal dedicated for rapid publication of high-quality, peer-reviewed research articles in fields covered by its title.

*Kybernetika* traditionally publishes research results in the fields of Control Sciences, Information Sciences, System Sciences, Statistical Decision Making, Applied Probability Theory, Random Processes, Fuzziness and Uncertainty Theories, Operations Research and Theoretical Computer Science, as well as in the topics closely related to the above fields.

The Journal has been monitored in the Science Citation Index since 1977 and it is abstracted/indexed in databases of Mathematical Reviews, Current Mathematical Publications, Current Contents ISI Engineering and Computing Technology.

---

*Kybernetika*. Volume 38 (2002)

ISSN 0023-5954, MK ČR E 4902.

Published bi-monthly by the Institute of Information Theory and Automation of the Academy of Sciences of the Czech Republic, Pod Vodárenskou věží 4, 182 08 Praha 8. — Address of the Editor: P. O. Box 18, 182 08 Prague 8, e-mail: kybernetika@utia.cas.cz. — Printed by PV Press, Pod vrstevnicí 5, 140 00 Prague 4. — Orders and subscriptions should be placed with: MYRIS TRADE Ltd., P. O. Box 2, V Štíhlách 1311, 142 01 Prague 4, Czech Republic, e-mail: myris@myris.cz. — Sole agent for all “western” countries: Kubon & Sagner, P. O. Box 34 01 08, D-8 000 München 34, F.R.G.

Published in October 2002.

© Institute of Information Theory and Automation of the Academy of Sciences of the Czech Republic, Prague 2002.

## RANK-ONE LMI APPROACH TO ROBUST STABILITY OF POLYNOMIAL MATRICES

DIDIER HENRION, KENJI SUGIMOTO AND MICHAEL ŠEBEK

Necessary and sufficient conditions are formulated for checking robust stability of an uncertain polynomial matrix. Various stability regions and uncertainty models are handled in a unified way. The conditions, stemming from a general optimization methodology similar to the one used in  $\mu$ -analysis, are expressed as a rank-one LMI, a non-convex problem frequently arising in robust control. Convex relaxations of the problem yield tractable sufficient LMI conditions for robust stability of uncertain polynomial matrices.

### 1. INTRODUCTION

Polynomial matrices play a central role in modern systems theory. Algebraic methods such as the polynomial approach [20] or the behavioral approach [28] heavily rely upon polynomial matrices. Dynamics of many systems (e. g. lightly damped structures such as oil derricks or regional power system models, see [19] and references therein) are most naturally represented by polynomial matrices and polynomial matrix fraction descriptions. Unsurprisingly, fundamental system features are captured by properties of polynomial matrices. For example, the zeros<sup>1</sup> of the denominator polynomial matrix in a matrix fraction description characterize system dynamics and performance. Satisfactory transient time response can be ensured as soon as the zeros are located in some specific region of the complex plane.

An important issue in control is to assess to what extent stability and performance of a system can be guaranteed in face of uncertainty or variation of the system parameters. A lot of research efforts has been recently devoted to the investigation of this problem, which has been coined out as the robust stability analysis problem, see e. g. the textbooks [2, 3, 29] and references therein. Quite naturally, the problem of checking robust stability of uncertain linear systems amounts to checking robust stability of uncertain polynomial matrices.

A very few works have been devoted so far to the study of robust stability of polynomial matrices, probably because the problem is particularly difficult to solve in its most general form. For example, it was proved that checking robust stability of a polytope of polynomial matrices (the so-called polytopic uncertainty model, see

---

<sup>1</sup>The zeros of a polynomial matrix are the roots of its determinant.

e.g. [2]) is an NP-hard problem even in the simple case that all vertex matrices are of degree zero (i.e. when they do not depend in the indeterminate) [4]. NP-hardness roughly means that it is very unlikely to find an algorithm that solves the problem in a time which is a polynomial function of the problem dimensions. These negative results have naturally led to the development of conservative, yet tractable, polynomial-time conditions for checking robust stability. One possibility is to strengthen the standard notions of stability and allowable uncertainty model [19]. Another possibility is to pursue the so-called quadratic stability approach in the context of Lyapunov theory [2, 11]. It paved the way for the development of efficient polynomial-time stability tests based on optimization over linear matrix inequalities (LMIs, see [5]). Such stability tests are based on sufficient stability conditions. That is to say, they may guarantee robust stability at the price of a certain amount of conservatism which is difficult to evaluate. Preliminary results on the application of LMI techniques to the study of robust stability of polytopes of polynomial matrices are reported in [17].

In view of this unsatisfactory state of the art, the paper is precisely an attempt to overcome the lack of sufficiently general methods for assessing robust stability of uncertain polynomial matrices. As an extension of the results presented in [17], we provide sufficient but also necessary robust stability conditions. Our approach is sufficiently general to handle in a unified way a fairly large number of uncertainty models and stability regions. The basic idea behind our approach can be found in [9] and can be traced back to  $\mu$ -analysis [10, 21]. It has been used recently to assess  $\mathcal{D}$ -stability of polynomial matrices [15] and stability of 2-D polynomial matrices [16]. The stability problem is first expressed as a quadratic optimization problem. Then, several techniques are used to come up with a standard form of the problem. The necessary and sufficient robust stability conditions are expressed as a rank-one LMI problem, a non-convex optimization problem frequently arising in robust control problems, see [14] and references therein. Convex relaxations of this non-convex rank-one LMI problem yield possibly conservative but tractable LMI conditions for robust stability.

The outline of the paper is as follows. In Section 2 we state the problem to be solved. Then we introduce the stability regions (Section 3) and uncertainty models (Section 4) considered in the paper. In Section 5 we derive a rank-one LMI formulation of the problem. An illustrative example is proposed in Section 6.

**Notations:**  $\mathbb{R}$  and  $\mathbb{C}$  are the sets of real and complex numbers, respectively.  $A^*$  means transpose conjugate of complex matrix  $A$ . The matrix inequalities  $A \succ B$  and  $A \succeq B$  mean that matrix  $A - B$  is positive definite and positive semidefinite, respectively.

## 2. PROBLEM STATEMENT

Suppose we are given a non-singular complex polynomial matrix

$$A(s, \Delta) = A_0(\Delta) + A_1(\Delta)s + \cdots + A_d(\Delta)s^d$$

of size  $n$  and degree  $d$ , whose matrix coefficients  $A_i(\Delta)$  are affected by some uncertainty  $\Delta \in \mathbf{\Delta}$  where  $\mathbf{\Delta}$  is a given set of allowable uncertainties. Suppose moreover that we are given a region  $\mathcal{D} \subset \mathbb{C}$  of the complex plane.

We say that uncertain polynomial matrix  $A(s, \Delta)$  is robustly  $\mathcal{D}$ -stable if and only if the zeros of  $A(s, \Delta)$  remain in region  $\mathcal{D}$  for all admissible values  $\Delta$  of the uncertainty. We aim at finding necessary and sufficient conditions for robust  $\mathcal{D}$ -stability of polynomial matrix  $A(s, \Delta)$ .

### 3. STABILITY REGIONS

First we describe the class of regions  $\mathcal{D}$  we will consider throughout the paper.

Define  $\mathcal{D}^C = \{s \in \mathbb{C} : s \notin \mathcal{D}\}$  as the complement of region  $\mathcal{D}$  in  $\mathbb{C}$ . In this paper, we restrict our attention to two-dimensional regions  $\mathcal{D}$  whose complement reads

$$\mathcal{D}^C = \{s \in \mathbb{C} : D^{00} + D^{01}s + D^{10}s^* + D^{11}ss^* \succeq 0\} \tag{1}$$

where Hermitian matrix

$$D = D^* = \begin{bmatrix} D^{00} & D^{01} \\ D^{10} & D^{11} \end{bmatrix}$$

is non-singular and has at least one negative eigenvalue. In [15] we show that the above description is fairly general and can cover half-planes, disks, ellipsoids, parabolas and their complements, or possibly non-connected unions. For the sake of simplicity, in this paper we restrict our attention to the following simple regions:

- Half-plane  $\mathcal{D} = \{x + jy \in \mathbb{C} : ax + by + c \geq 0\}$  with  $a, b, c \in \mathbb{R}$  and

$$D = \begin{bmatrix} 2c & a + jb \\ a - jb & 0 \end{bmatrix}.$$

- Disk  $\mathcal{D} = \{s \in \mathbb{C} : |s - s_0| \leq r\}$  with  $s_0 \in \mathbb{C}$ ,  $r > 0 \in \mathbb{R}$  and

$$D = \begin{bmatrix} r^2 - s_0s_0^* & s_0 \\ s_0^* & -1 \end{bmatrix}.$$

- Disk complement  $\mathcal{D} = \{s \in \mathbb{C} : |s - s_0| \geq r\}$  with  $s_0 \in \mathbb{C}$ ,  $r > 0 \in \mathbb{R}$  and

$$D = \begin{bmatrix} -r^2 + s_0s_0^* & -s_0 \\ -s_0^* & 1 \end{bmatrix}.$$

where  $2 \times 2$  matrix  $D$  has exactly one negative eigenvalue and one positive eigenvalue. Note that some care must be taken with zeros at infinity when dealing with open stability regions such as the disk complement or the left half-plane, see [15, § 3] for details.

4. UNCERTAINTY MODELS

In this section, we describe the class of allowable uncertainties studied in the paper.

We consider that uncertainty  $\Delta$  has a block-diagonal structure, a standard assumption made in the robust control literature, i. e.

$$\Delta = \begin{bmatrix} \Delta_1 & & & 0 \\ & \Delta_2 & & \\ & & \ddots & \\ 0 & & & \Delta_K \end{bmatrix}.$$

Each sub-block  $\Delta_i$  belongs to  $\mathbb{C}^{N_i \times N_i}$ . This allows us to write uncertain polynomial matrix  $A(s, \Delta)$  using a Linear Fractional Representation (LFR)

$$A(s, \Delta) = A_0 + L\Delta_s(I_N - D\Delta_s)^{-1}R \tag{2}$$

where the indeterminate  $s$  has been incorporated into

$$\Delta_s = \begin{bmatrix} sI_{dn} & 0 \\ 0 & \Delta \end{bmatrix}$$

so that  $N = dn + N_1 + \dots + N_K$  [29]. For a given index  $i$ , a rather large set of uncertainties can be captured by the quadratic description

$$\Delta_i = \{\Delta_i \in \mathbb{C}^{N_i \times N_i} : D_i^{00} + D_i^{01}\Delta_i + \Delta_i^*D_i^{10} + \Delta_i^*D_i^{11}\Delta_i \succeq 0\}$$

where Hermitian matrix

$$D_i = D_i^* = \begin{bmatrix} D_i^{00} & D_i^{01} \\ D_i^{10} & D_i^{11} \end{bmatrix}$$

is non-singular and has at least one negative eigenvalue. Note that this class of uncertainties is similar to the stability regions considered in Section 3. In [25], this class is referred to as  $\{X, Y, Z\}$ -dissipative uncertainties (with an additional sign assumption on  $D_i^{11}$ ).

In this paper, we restrict ourselves to the following uncertainty models:

- Norm-bounded uncertainties, with

$$\Delta_i = \{\Delta_i \in \mathbb{C}^{N_i \times N_i} : \|\Delta_i\|_2 \leq \gamma_i\}$$

and

$$D_i = \begin{bmatrix} \gamma_i^2 I_{N_i} & 0 \\ 0 & -I_{N_i} \end{bmatrix}.$$

- Interval uncertainties, with

$$\Delta_i = \{\Delta_i = (x_i + jy_i)I_{N_i} \in \mathbb{C}^{N_i \times N_i} : x_i \in [a_i, b_i]\}$$

and

$$D_i = \begin{bmatrix} -2ab & a + b \\ a + b & -2 \end{bmatrix}.$$

Using the same formalism, we can also cope with positive-real uncertainties, sector-bounded uncertainties or  $\beta$ -bounded uncertainties [12, 13, 26]. We can also enforce the uncertain parameters to be purely real (using a technique similar to that exposed in [10]) but it is out of the scope of the present paper.

## 5. RANK-ONE LMI FORMULATION OF THE PROBLEM

Following these preliminaries, we can now derive a rank-one LMI formulation of a necessary and sufficient condition for robust stability of a polynomial matrix.

Our approach is twofold. First in Paragraph 5.1 we show that checking robust stability amounts to solving a quadratic optimization problem. Second, the LFR of  $A(s, \Delta)$  is used in Paragraph 5.2 to take advantage of the special quadratic structure of the optimization problem and to derive an LMI formulation where all the non-convexity is concentrated into the constraint that a matrix has rank one. Convex primal and dual LMI relaxations are then proposed in Paragraph 5.3 and 5.4 respectively.

### 5.1. Quadratic optimization problem

Recall from the problem statement in Section 2 that robust stability of uncertain polynomial matrix  $A(s, \Delta)$  holds if and only if its zeros remain in  $\mathcal{D}$  for all uncertainty  $\Delta \in \mathbf{\Delta}$ , or equivalently, if and only if  $A(s, \Delta)v \neq 0$  for all non-zero  $v \in \mathbb{C}^n$ ,  $s \in \mathcal{D}^C$  and  $\Delta \in \mathbf{\Delta}$ . Robust stability is then ensured if and only if the optimal value  $\mu$  of the quadratic optimization problem

$$\begin{aligned} \mu &= \min_{\substack{s \in \mathcal{D}^C \\ \Delta \in \mathbf{\Delta} \\ v^*v = 1}} v^* A^*(s, \Delta) A(s, \Delta) v \end{aligned} \quad (3)$$

is strictly positive.

### 5.2. Rank-one LMI problem

Now we show that solving quadratic optimization problem (3) amounts to solving a rank-one LMI optimization problem.

In relation with the LFR (2) of matrix  $A(s, \Delta)$ , we can define vectors

$$p = \begin{bmatrix} p_0 \\ p_1 \\ \vdots \\ p_K \end{bmatrix} \quad q = \begin{bmatrix} q_0 \\ q_1 \\ \vdots \\ q_K \end{bmatrix}$$

such that

$$\begin{aligned} A(s, \Delta)v &= A_0v + Lp \\ q &= Rv + Dp \\ p &= \Delta_s q. \end{aligned} \quad (4)$$

For any sub-vectors  $p_i, q_i$  in  $p, q$ , it follows from the block-diagonal structure of  $\Delta_s$  that

$$p_i = \Delta_i q_i. \tag{5}$$

Now define the rank-one positive semidefinite matrix

$$X = xx^* = \begin{bmatrix} v \\ p \end{bmatrix} \begin{bmatrix} v \\ p \end{bmatrix}^* \succeq 0 \tag{6}$$

and matrices  $\mathcal{A}, \mathcal{P}_i$  and  $\mathcal{Q}_i$  such that

$$\begin{aligned} A(\Delta_s)v &= \mathcal{A}x \\ q_i &= \mathcal{Q}_i x \\ p_i &= \mathcal{P}_i x \end{aligned}$$

for  $i = 0, 1, \dots, K$ . Define finally the partitioning

$$\begin{bmatrix} X_i^{00} & X_i^{01} \\ X_i^{10} & X_i^{11} \end{bmatrix} = \begin{bmatrix} \mathcal{Q}_i \\ \mathcal{P}_i \end{bmatrix} X \begin{bmatrix} \mathcal{Q}_i \\ \mathcal{P}_i \end{bmatrix}^*$$

and the linear maps  $F_i$  from  $\mathbb{C}^{N \times N}$  to  $\mathbb{C}^{M_i \times M_i}$  associated with sets  $\Delta_i$  as follows [9]:

- Stability region  $\Delta_i = \{sI_{N_i} \in \mathbb{C}^{N_i \times N_i} : D^{00} + D^{01}s + D^{10}s^* + D^{11}s^*s \geq 0\}$

$$F_i(X) = D^{00}X_i^{00} + D^{01}X_i^{10} + D^{10}X_i^{01} + D^{11}X_i^{11}.$$

- Norm-bounded uncertainties  $\Delta_i = \{\Delta_i \in \mathbb{C}^{N_i \times N_i} : \|\Delta_i\|_2 \leq \gamma_i\}$

$$F_i(X) = \text{trace}(\gamma_i^2 X_i^{00} - X_i^{11}).$$

- Interval uncertainties  $\Delta_i = \{(x_i + jy_i)I_{N_i} \in \mathbb{C}^{N_i \times N_i} : x_i \in [a_i, b_i]\}$

$$F_i(X) = -2a_i b_i X_i^{00} + (a_i + b_i)(X_i^{01} + X_i^{10}) - 2X_i^{11}.$$

In relation to the above linear maps, equation (5) and rank-one matrix (6), we can state the following central result.

**Lemma 1.** Assume vector  $q_i$  is non-zero. It holds  $p_i = \Delta_i q_i$  for some  $\Delta_i \in \Delta_i$  if and only if

$$F_i(X) \succeq 0. \tag{7}$$

*Proof.* This is a standard result in  $\mu$ -analysis, see [10, 21]. The proof is not reproduced here for conciseness. □

Using equations (4), (6), Lemma 1 and gathering all linear maps  $F_i(X)$  into one block-diagonal linear map

$$F(X) = \begin{bmatrix} F_0(X) & & & \\ & F_1(X) & & \\ & & \ddots & \\ & & & F_K(X) \end{bmatrix},$$

an alternative formulation of problem (3) can now be derived. It reads

$$\begin{aligned} \mu &= \min \quad \text{trace } \mathcal{A}^* \mathcal{A} X \\ &\text{s.t.} \quad F(X) \succeq 0 \\ &\quad X = X^* \succeq 0 \\ &\quad \text{rank } X = 1 \\ &\quad \text{trace} \begin{bmatrix} I_n & 0 \\ 0 & 0 \end{bmatrix} X = 1. \end{aligned} \tag{8}$$

Problem (8) is an LMI optimization problem with a non-convex rank constraint. It must be pointed out that rank-constrained LMIs frequently arise in control problems but also in mathematical programming and combinatorial optimization, see [14] for a recent overview. We have shown the main result of this paper.

**Theorem 1.** Polynomial matrix  $A(s, \Delta)$  is robustly  $\mathcal{D}$ -stable if and only if  $\mu > 0$  in rank-one LMI optimization problem (8).

### 5.3. Primal LMI relaxation

A convex primal LMI relaxation can readily be derived for non-convex rank-constrained LMI problem (8). As a result, we obtain a sufficient condition of robust  $\mathcal{D}$ -stability of polynomial matrix  $A(s, \Delta)$ .

Consider the following convex relaxation of rank-one LMI problem (8)

$$\begin{aligned} \nu &= \min \quad \text{trace } \mathcal{A}^* \mathcal{A} X \\ &\text{s.t.} \quad F(X) \succeq 0 \\ &\quad X = X^* \succeq 0 \\ &\quad \text{trace} \begin{bmatrix} I_n & 0 \\ 0 & 0 \end{bmatrix} X = 1 \end{aligned} \tag{9}$$

where the non-convex rank constraint has been dropped. Since the feasible set of problem (8) is included in the feasible set of problem (9),  $\nu > 0$  in problem (9) obviously implies  $\mu > 0$  in problem (8). This is captured in the following corollary to Theorem 1.

**Corollary 1.** Polynomial matrix  $A(s, \Delta)$  is robustly  $\mathcal{D}$ -stable if  $\nu > 0$  in LMI optimization problem (9).



**5.4. Dual LMI relaxation**

Now we propose a convex dual LMI relaxation for non-convex rank-constrained LMI problem (8).

For  $i = 0, 1, \dots, K$  define the linear maps  $F_i^D(P_i)$  dual to the maps  $F_i(X)$  introduced above, i. e. such that for any couple of matrices  $X \in \mathbb{C}^{N \times N}$  and  $P_i \in \mathbb{C}^{M_i \times M_i}$ , it holds

$$\text{trace } F_i^D(P_i)X = \text{trace } F_i(X)P_i.$$

Then define

$$P = \begin{bmatrix} P_0 & & & \\ & P_1 & & \\ & & \ddots & \\ & & & P_K \end{bmatrix}$$

and the associated linear map

$$F^D(P) = F_0^D(P_0)X + F_1^D(P_1)X + \dots + F_K^D(P_K)X.$$

Consider the LMI feasibility problem

$$\begin{aligned} \mathcal{A}^* \mathcal{A} &\succ F^D(P) \\ P &= P^* \succ 0 \end{aligned} \tag{10}$$

and note that as soon as the above problem is feasible, it holds

$$\text{trace } \mathcal{A}^* \mathcal{A} X > \text{trace } F^D(P)X = \text{trace } F(X)P$$

for any matrix  $X = X^* \succeq 0$ . Since the above inequality is also valid for any rank-one matrix  $X$ , it follows that  $\mu > 0$  in problem (8).

Using standard semi-definite programming duality arguments [27] it can be shown that LMI feasibility problem (10) is actually dual to relaxed LMI problem (9). Now if  $\mathcal{N}$  denotes a matrix whose columns span the right null-space of  $\mathcal{A}$ , it follows from the Elimination Lemma [5] that feasibility problem (10) can equivalently be written as

$$\begin{aligned} \mathcal{N}^* F^D(P) \mathcal{N} &\prec 0 \\ P &= P^* \succ 0. \end{aligned} \tag{11}$$

The following corollary to Theorem 1 follows from the above discussion and provides us with an equivalent sufficient condition of robust  $\mathcal{D}$ -stability.

**Corollary 2.** Polynomial matrix  $A(s, \Delta)$  is robustly  $\mathcal{D}$ -stable if there is a matrix  $P$  solution to LMI feasibility problem (11).

6. ILLUSTRATION

Let

$$A(s, \Delta) = \underbrace{\begin{bmatrix} 1 & 2 \\ 4 & 0 \end{bmatrix}}_{A_0} + \left( \underbrace{\begin{bmatrix} 0 & 0 \\ -1 & 0 \end{bmatrix}}_{A_1} + x_1 \underbrace{\begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}}_{B_1} \right) s + \left( \underbrace{\begin{bmatrix} -1 & -1 \\ 0 & 1 \end{bmatrix}}_{A_2} + \Delta_2 \right) s^2$$

be a polynomial matrix affected by interval uncertainty

$$x_1 \in [-0.6000, 0.6000] = [a_1, b_1]$$

and norm-bounded uncertainty

$$\|\Delta_2\|_2 \leq \gamma_2 = 0.3000.$$

We are interested in knowing whether the zeros of polynomial matrix  $A(s, \Delta)$  stay outside of the closed unit disk

$$\mathcal{D}^C = \{s \in \mathbb{C} : s^*s \leq 1\}.$$

for all admissible uncertainty.

Defining

$$\Delta_s = \begin{bmatrix} sI_4 & & \\ & x_1I_2 & \\ & & \Delta_2 \end{bmatrix}$$

and using the construction principle described in [29], one possible LFR (2) for the above polynomial matrix is given by

$$\left[ \begin{array}{c|c} A_0 & L \\ \hline R & D \end{array} \right] = \left[ \begin{array}{c|ccccc} A_0 & A_1 & A_2 & B_1 & I_2 \\ \hline I_2 & 0 & 0 & 0 & 0 \\ 0 & I_2 & 0 & 0 & 0 \\ 0 & I_2 & 0 & 0 & 0 \\ 0 & 0 & I_2 & 0 & 0 \end{array} \right].$$

Projection matrices in LMI problem (9) are as follows

$$\begin{aligned} \mathcal{Q}_0 &= \begin{bmatrix} I_2 & 0 & 0 & 0 & 0 \\ 0 & I_2 & 0 & 0 & 0 \end{bmatrix} & \mathcal{P}_0 &= \begin{bmatrix} 0 & I_2 & 0 & 0 & 0 \\ 0 & 0 & I_2 & 0 & 0 \end{bmatrix} \\ \mathcal{Q}_1 &= \begin{bmatrix} 0 & I_2 & 0 & 0 & 0 \end{bmatrix} & \mathcal{P}_1 &= \begin{bmatrix} 0 & 0 & 0 & I_2 & 0 \end{bmatrix} \\ \mathcal{Q}_2 &= \begin{bmatrix} 0 & 0 & I_2 & 0 & 0 \end{bmatrix} & \mathcal{P}_2 &= \begin{bmatrix} 0 & 0 & 0 & 0 & I_2 \end{bmatrix}. \end{aligned}$$

With the notation

$$\mathcal{A} = [ A_0 \quad A_1 \quad A_2 \quad B_1 \quad I_2 ],$$

LMI optimization problem (9) reads

$$\begin{aligned}
 \nu &= \min \operatorname{trace} \mathcal{A}^* \mathcal{A} X \\
 \text{s.t. } & F_0(X) = \mathcal{Q}_0 X \mathcal{Q}_0^* - \mathcal{P}_0 X \mathcal{P}_0^* \succeq 0 \\
 & F_1(X) = -2a_1 b_1 \mathcal{Q}_1 X \mathcal{Q}_1^* + (a_1 + b_1)(\mathcal{Q}_1 X \mathcal{P}_1^* + \mathcal{P}_1 X \mathcal{Q}_1^*) - 2\mathcal{P}_1 X \mathcal{Q}_1^* \succeq 0 \\
 & F_2(X) = \operatorname{trace}(-\mathcal{P}_2 X \mathcal{P}_2^* + \gamma_2^2 \mathcal{Q}_2 X \mathcal{Q}_2^*) \succeq 0 \\
 & \operatorname{trace} \begin{bmatrix} I_2 & 0 \\ 0 & 0 \end{bmatrix} X = 1, \quad X = X^* \succeq 0.
 \end{aligned}$$

With the help of the interior-point algorithm of the SDPHA package 3.0 [6] called from the user-friendly interface LMITOOL 2.0 for MATLAB [8] we obtained

$$\nu = 0.004635$$

as the optimal value of the above problem, with

$$X = \begin{bmatrix}
 0.1562 & -0.3551 & 0.1556 & -0.3602 & 0.1539 & -0.3628 & -0.0934 & 0.2082 & 0.1116 & -0.0106 \\
 -0.3551 & 0.8438 & -0.3473 & 0.8407 & -0.3371 & 0.8316 & 0.2162 & -0.5043 & -0.2720 & 0.0205 \\
 0.1556 & -0.3473 & 0.1562 & -0.3551 & 0.1556 & -0.3602 & -0.0923 & 0.2021 & 0.1079 & -0.0112 \\
 -0.3602 & 0.8407 & -0.3551 & 0.8438 & -0.3473 & 0.8407 & 0.2177 & -0.4987 & -0.2683 & 0.0223 \\
 0.1539 & -0.3371 & 0.1556 & -0.3473 & 0.1562 & -0.3551 & -0.0906 & 0.1944 & 0.1035 & -0.0117 \\
 -0.3628 & 0.8316 & -0.3602 & 0.8407 & -0.3551 & 0.8438 & 0.2176 & -0.4895 & -0.2626 & 0.0240 \\
 -0.0934 & 0.2162 & -0.0923 & 0.2177 & -0.0906 & 0.2176 & 0.0562 & -0.1278 & -0.0687 & 0.0060 \\
 0.2082 & -0.5043 & 0.2021 & -0.4987 & 0.1944 & -0.4895 & -0.1278 & 0.3038 & 0.1643 & -0.0111 \\
 0.1116 & -0.2720 & 0.1079 & -0.2683 & 0.1035 & -0.2626 & -0.0687 & 0.1643 & 0.0889 & -0.0058 \\
 -0.0106 & 0.0205 & -0.0112 & 0.0223 & -0.0117 & 0.0240 & 0.0060 & -0.0111 & -0.0058 & 0.0011
 \end{bmatrix}.$$

In virtue of Corollary 1,  $\nu > 0$  implies that  $A(s, \Delta)$  has no zero within the closed unit disk for any admissible uncertain parameters  $x_1$  and  $\Delta_2$ . Hence polynomial matrix  $A(s, \Delta)$  is robustly  $\mathcal{D}$ -stable. This can be checked graphically in Figure 1, where zeros of  $A(s, \Delta)$  are represented for 1000 randomly chosen admissible uncertain parameters.

Now if we set


$$\gamma_2 = 0.4000$$

the optimal value of LMI problem (9) is

$$\nu = 5.2982 \cdot 10^{-10} \approx 0$$

for

$$X = \begin{bmatrix}
 0.1423 & -0.3261 & 0.1256 & -0.2777 & 0.1357 & -0.3425 & -0.0794 & 0.1819 & 0.1212 & -0.0215 \\
 -0.3261 & 0.8577 & -0.2500 & 0.5999 & -0.2842 & 0.8230 & 0.1995 & -0.5045 & -0.3460 & 0.0319 \\
 0.1256 & -0.2500 & 0.1412 & -0.3250 & 0.1249 & -0.2771 & -0.0628 & 0.1345 & 0.0878 & -0.0214 \\
 -0.2777 & 0.5999 & -0.3250 & 0.8550 & -0.2497 & 0.5998 & 0.1477 & -0.3427 & -0.2293 & 0.0382 \\
 0.1357 & -0.2842 & 0.1249 & -0.2497 & 0.1395 & -0.3231 & -0.0705 & 0.1509 & 0.0984 & -0.0242 \\
 -0.3425 & 0.8230 & -0.2771 & 0.5998 & -0.3231 & 0.8505 & 0.1961 & -0.4639 & -0.3122 & 0.0464 \\
 -0.0794 & 0.1995 & -0.0628 & 0.1477 & -0.0705 & 0.1961 & 0.0490 & -0.1160 & -0.0781 & 0.0096 \\
 0.1819 & -0.5045 & 0.1345 & -0.3427 & 0.1509 & -0.4639 & -0.1160 & 0.3049 & 0.2093 & -0.0131 \\
 0.1212 & -0.3460 & 0.0878 & -0.2293 & 0.0984 & -0.3122 & -0.0781 & 0.2093 & 0.1477 & -0.0070 \\
 -0.0215 & 0.0319 & -0.0214 & 0.0382 & -0.0242 & 0.0464 & 0.0096 & -0.0131 & -0.0070 & 0.0087
 \end{bmatrix}.$$



**Fig. 1.** Case  $\gamma_2 = 0.3000$ . Zeros of  $A(s, \Delta)$  for 1000 randomly chosen admissible uncertain parameters  $x_1$  and  $\Delta_2$ .

However, Corollary 1 cannot be used to conclude about robust stability or instability of polynomial matrix  $A(s, \Delta)$ .

Using a trial and error method, we found that matrix  $A(s, \Delta)$  has an unstable zero at  $\bar{s} = 0.9903$  for the following choice of admissible uncertain parameters

$$\bar{x}_1 = -0.6000 \quad \bar{\Delta}_2 = \begin{bmatrix} 0.1600 & -0.3600 \\ 0.0800 & 0.0400 \end{bmatrix}.$$

The normalized vector  $\bar{v}$  such that  $(A_0 + (A_1 + \bar{x}_1)\bar{s} + (A_2 + \bar{\Delta}_2)\bar{s}^2)\bar{v} = 0$  gives rises to a vector

$$x = \begin{bmatrix} \bar{v} \\ \bar{s}\bar{v} \\ \bar{s}^2\bar{v} \\ \bar{x}_1\bar{s}\bar{v} \\ \bar{\Delta}_2\bar{s}^2\bar{v} \end{bmatrix} = \begin{bmatrix} -0.3785 \\ 0.9256 \\ -0.3749 \\ 0.9166 \\ -0.3712 \\ 0.9077 \\ 0.2249 \\ -0.5500 \\ -0.3862 \\ 0.0066 \end{bmatrix}$$

such that rank-one matrix  $X = xx'$  satisfies  $\mu = 0$  in rank-constrained LMI problem (8). In virtue of Theorem 1, uncertain polynomial matrix  $A(s, \Delta)$  is not robustly  $\mathcal{D}$ -stable.

## 7. CONCLUSION

Following an idea found in [9, Chapter 1] and that can be traced back to  $\mu$ -analysis [10, 21], we have proposed a general methodology for determining whether the zeros of a given uncertain polynomial matrix stay within a given region of the complex plane for all admissible uncertainty. Several stability regions and uncertainty models can be covered in a unified way. Necessary and sufficient conditions are formulated as a rank-constrained LMI optimization problem. Sufficient robust stability conditions are readily derived as convex LMI optimization or feasibility problems.

The main motivation behind formulating the robust stability problem as a rank-constrained LMI problem is in that our results can be extended in various directions:

- Necessary robust stability conditions may also be obtained, using geometric properties of the intersection of ellipsoids [14].
- The gap between necessity and sufficiency of the LMI conditions can be narrowed thanks to recent results on the full-block  $\mathcal{S}$ -procedure [24] and quadratic separators [18, 22].
- Rank-one LMI problems are special kinds of non-convex optimization problems for which tailored global optimization algorithms have recently been designed [1]. Quite efficient local optimization algorithms based on successive linearizations can also be used [7], but without guarantee of convergence to the global optimum.
- The LFR used to represent the uncertain polynomial matrix is not necessarily minimal, thus problem dimensions in the LMIs can be decreased via any (sub-optimal) LFR reduction procedure (see [15, 16] for an example of such a procedure).
- Numerical aspects of solving the LMI conditions must also be carefully checked. Intensive numerical experiments are currently performed and will result in several new macros to be implemented in the next release 3.0 of the Polynomial Toolbox for MATLAB, see [23].
- Another interesting extension could eventually be to consider robust synthesis problems and Diophantine equations over polynomial matrices [20].

## ACKNOWLEDGEMENTS

Most of this work was done when the first and third authors were visiting the Department of Aerospace Engineering at the University of Nagoya, Japan, in the scope of the Japanese–Czech project “Polynomial Methods for Industrial Control Design” sponsored by the Programme “Contact” of the Czech Ministry of Education under project No. NJ 11/98. These authors would particularly like to thank Professors M. Suzuki and K. Sugimoto for their genuine sense of hospitality. The first author is also grateful to Denis Arzelier and Dimitry Peaucelle, LAAS–CNRS, Toulouse, for several stimulating discussions. This work was also supported by the Ministry of Education of the Czech Republic under contract No. LN00B096.

(Received February 4, 2002.)

## REFERENCES

- 
- [1] P. Apkarian and H.D. Tuan: A sequential SDP/Gauss–Newton algorithm for rank-constrained LMI problems. In: Proc. IEEE Conference on Decision and Control, Phoenix 1999, pp. 2328–2333.
  - [2] B.R. Barmish: *New Tools for Robustness of Linear Systems*. Macmillan, New York 1994.
  - [3] S.P. Bhattacharyya, H. Chapellat, and L.H. Keel: *Robust Control: The Parametric Approach*. Prentice Hall, Upper Saddle River, N.J. 1995.
  - [4] V.D. Blondel and J.N. Tsitsiklis: A survey of computational complexity results in systems and control. *Automatica* 36 (2000), 9, 1249–1274.
  - [5] S. Boyd, L. El Ghaoui, E. Feron, and V. Balakrishnan: *Linear Matrix Inequalities in System and Control Theory*. SIAM Studies in Applied Mathematics, Philadelphia 1994.
  - [6] N. Brixius, R. Sheng, and F.A. Potra: SDPHA: a MATLAB implementation of homogeneous interior-point algorithms for semidefinite programming. *Optimization Methods and Software* 11/12 (1999), 583–596.
  - [7] L. El Ghaoui, F. Oustry, and M. Ait Rami: A cone complementarity linearization algorithm for static output feedback and related problems. *IEEE Trans. Automat. Control* 42 (1997), 8, 1171–1176.
  - [8] L. El Ghaoui and J.L. Commeau: LMITOOL 2.0 Package: An Interface to Solve LMI Problems. *E-Letters on Systems, Control and Signal Processing*, Issue 125, January 1999.
  - [9] L. El Ghaoui and S.I. Niculescu (eds.): *Advances in Linear Matrix Inequality Methods in Control*. SIAM Advances in Control and Design, Philadelphia, 1999.
  - [10] M. Fan, A. Tits, and J. Doyle: Robustness in the presence of joint parametric uncertainty and unmodeled dynamics. *IEEE Trans. Automat. Control* 36 (1991), 1, 25–38.
  - [11] J.C. Geromel, P.L.D. Peres, and J. Bernussou: On a convex parameter space method for linear control design of uncertain systems. *SIAM J. Control Optim.* 29 (1991), 381–402.
  - [12] S. Gupta: Robust stability analysis using LMI: Beyond small gain and passivity. *Internat. J. Robust Nonlinear Control* 6 (1996), 953–968.
  - [13] W.M. Haddad and D.S. Bernstein: Explicit construction of quadratic Lyapunov functions for the small gain, positivity, circle and Popov theorems and their applications to robust stability. Part I: Continuous-time theory. *Internat. J. Robust Nonlinear Control* 3 (1993), 313–339.
  - [14] D. Henrion, S. Tarbouriech, and M. Šebek: Rank-one LMI approach to simultaneous stabilization of linear systems. *Systems Control Lett.* 38 (1999), 2, 79–89.
  - [15] D. Henrion, O. Bachelier, and M. Šebek:  $\mathcal{D}$ -stability of polynomial matrices. *Internat. J. Control* 74 (2001), 8, 845–856.
  - [16] D. Henrion, M. Šebek, and O. Bachelier: Rank-one LMI approach to stability of 2-D polynomial matrices. *Multidimensional Systems and Signal Processing* 12 (2001), 1, 33–48.
  - [17] D. Henrion, D. Arzelier, D. Peaucelle, and M. Šebek: An LMI condition for robust stability of polynomial matrix polytopes. *Automatica* 37 (2001), 3, 461–468.
  - [18] T. Iwasaki and S. Hara: Well-posedness of feedback systems: Insights into exact robustness analysis and approximate computations. *IEEE Trans. Automat. Control* 43 (1998), 5, 619–630.

- [19] W.C. Karl and G.C. Verghese: A sufficient condition for the stability of interval matrix polynomials. *IEEE Trans. Automat. Control* 38 (1993), 7, 1139–1143.
- [20] V. Kučera: *Discrete Linear Control: The Polynomial Approach*. Wiley, Chichester 1979.
- [21] A. Packard and J. Doyle: The complex singular value. *Automatica* 29 (1993), 1, 71–109.
- [22] D. Peaucelle and D. Arzelier: New LMI-based conditions for robust  $\mathcal{H}_2$  performance analysis: In *Proc. American Control Conference, Chicago 2000*, pp. 317–321.
- [23] Polyx, Inc.: *Polynomial Toolbox for MATLAB*, Release 2.0.0, 1999. See the web page [www.polyx.cz](http://www.polyx.cz).
- [24] C. Scherer: A full-block  $S$ -procedure with applications: In: *Proc. IEEE Conference on Decision and Control, San Diego 1997*, pp. 2602–2607.
- [25] G. Scorletti and L. El Ghaoui: Improved LMI conditions for gain scheduling and related control problems: *Internat. J. Robust Nonlinear Control* 8 (1998), 845–877.
- [26] D. Shim: Quadratic stability in the circle theorem or positivity theorem. *Internat. J. Robust Nonlinear Control* 6 (1996), 781–788.
- [27] L. Vandenberghe and S. Boyd: Semidefinite programming. *SIAM Rev.* 38 (1996), 49–95.
- [28] J.C. Willems: Paradigms and puzzles in the theory of dynamical systems. *IEEE Trans. Automat. Control* 36 (1991), 259–294.
- [29] K. Zhou, J. Doyle, and K. Glover: *Robust and Optimal Control*. Prentice Hall, Upper Saddle River, N.J. 1996.

*Dr. Didier Henrion, Laboratoire d'Analyse et d'Architecture des Systèmes, Centre National de la Recherche Scientifique, 7 avenue du Colonel Roche, 31 077 Toulouse, cedex 4, France and Institute of Information Theory and Automation – Academy of Sciences of the Czech Republic, Pod vodárenskou věží 4, 182 08 Praha 8, Czech Republic.  
e-mail: henrion@laas.fr.*

*Dr. Kenji Sugimoto, Department of Information Systems, Nara Institute of Science and Technology, Takayama 8916-5, Ikoma, Nara 630-0101. Japan.  
e-mail: kenji@is.aist-nara.ac.jp*

*Ing. Michael Šebek, DrSc., Center for Applied Cybernetics, Faculty of Electrical Engineering, Czech Technical University in Prague, Technická 2, 166 27 Praha 6. Czech Republic.  
e-mail: m.sebek@c-a-k.cz*