

On weak (measure-valued) solution approach to problems in fluid mechanics

Eduard Feireisl

based on joint work with J.Březina (Tokio), C.Klingenberg, and S.Markfelder (Wuerzburg), O.Kreml (Praha), M. Lukáčová (Mainz), H.Mizerová (Bratislava), A.Novotný (Toulon)

Institute of Mathematics, Academy of Sciences of the Czech Republic, Prague

Differential Equations Workshop, CEU Budapest, April 4–6, 2018

The research leading to these results has received funding from the European Research Council under the European Union's Seventh Framework Programme (FP7/2007-2013)/ ERC Grant Agreement 320078

Motivation - Complete Euler system

Phase variables

mass density $\varrho = \varrho(t, x)$, $t \in (0, T)$, $x \in \Omega \subset \mathbb{R}^3$

(absolute) temperature $\vartheta = \vartheta(t, x)$, $t \in (0, T)$, $x \in \Omega \subset \mathbb{R}^3$

(bulk) velocity field $\mathbf{u} = \mathbf{u}(t, x)$, $t \in (0, T)$, $x \in \Omega \subset \mathbb{R}^3$

Standard formulation

$$\partial_t \varrho + \operatorname{div}_x(\varrho \mathbf{u}) = 0$$

$$\partial_t(\varrho \mathbf{u}) + \operatorname{div}_x(\varrho \mathbf{u} \otimes \mathbf{u}) + \nabla_x p(\varrho, \vartheta) = 0$$

$$\partial_t \left(\frac{1}{2} \varrho |\mathbf{u}|^2 + \varrho e(\varrho, \vartheta) \right) + \operatorname{div}_x \left[\left(\frac{1}{2} \varrho |\mathbf{u}|^2 + \varrho e(\varrho, \vartheta) + p(\varrho, \vartheta) \right) \mathbf{u} \right] = 0$$

Impermeability condition

$$\mathbf{u} \cdot \mathbf{n}|_{\partial\Omega} = 0$$

Complete Euler system in conservative variables

Conservative variables

mass density $\varrho = \varrho(t, x)$, $t \in (0, T)$, $x \in \Omega \subset \mathbb{R}^3$

(total energy) $E = E(t, x)$, $t \in (0, T)$, $x \in \Omega \subset \mathbb{R}^3$

momentum $\mathbf{m} = \mathbf{m}(t, x)$, $t \in (0, T)$, $x \in \Omega \subset \mathbb{R}^3$

$$p = (\gamma - 1)\varrho e, \quad p = (\gamma - 1) \left(E - \frac{1}{2} \frac{|\mathbf{m}|^2}{\varrho} \right)$$

Field equations

$$\partial_t \varrho + \operatorname{div}_x \mathbf{m} = 0$$

$$\partial_t \mathbf{m} + \operatorname{div}_x \left(\frac{\mathbf{m} \otimes \mathbf{m}}{\varrho} \right) + \nabla_x p = 0$$

$$\partial_t E + \operatorname{div}_x \left[(E + p) \frac{\mathbf{m}}{\varrho} \right] = 0$$

Entropy

Gibbs' relation

$$\vartheta Ds = De + pD\left(\frac{1}{\varrho}\right)$$

Entropy balance

$$\partial_t(\varrho s) + \operatorname{div}_x(\mathbf{sm}) \boxed{\geq} 0$$

Entropy in the polytropic case

$$s = S\left(\frac{p}{\varrho^\gamma}\right) = S\left((\gamma - 1) \frac{E - \frac{1}{2} \frac{|\mathbf{m}|^2}{\varrho}}{\varrho^\gamma}\right)$$

Several concepts of solutions

Classical solutions

The phase variables are smooth (differentiable), the equations are satisfied in the standard sense. Classical solutions are often uniquely determined by the data. The main issue here is global in time existence that may fail for generic initial data

Weak (distributional) solutions

Limits of classical solutions, limits of regularized problems. Equations are satisfied in the distributional sense. Weak solutions may not be uniquely determined by the data.

Viscosity solutions

Limits of the Navier-Stokes-Fourier system for vanishing transport coefficients.

Limits of approximate (numerical) schemes

Zero step limits of numerical schemes. Examples are Lax-Friedrichs and related schemes mimicking certain approximations - e.g. a model proposed by H. Berner.

Admissible (entropy) weak solutions

Field equations

$$\left[\int_{\Omega} \varrho \varphi \, dx \right]_{t=0}^{t=\tau} = \int_0^{\tau} \int_{\Omega} [\varrho \partial_t \varphi + \varrho \mathbf{u} \cdot \nabla_x \varphi] \, dx dt$$

for all $\varphi \in C^1([0, T] \times \bar{\Omega})$

$$\left[\int_{\Omega} \mathbf{m} \cdot \varphi \, dx \right]_{t=0}^{t=\tau} = \int_0^{\tau} \int_{\Omega} \left[\mathbf{m} \cdot \partial_t \varphi + \frac{\mathbf{m} \otimes \mathbf{m}}{\varrho} : \nabla_x \varphi + p \operatorname{div}_x \varphi \right] \, dx dt$$

for all $\varphi \in C^1([0, T] \times \bar{\Omega}; \mathbb{R}^3)$, $\varphi \cdot \mathbf{n}|_{\partial\Omega} = 0$

$$\left[\int_{\Omega} E \varphi \, dx \right]_{t=0}^{t=\tau} = \int_0^{\tau} \int_{\Omega} \left[E \partial_t \varphi + \left[(E + p) \frac{\mathbf{m}}{\varrho} \right] \cdot \nabla_x \varphi \right] \, dx dt$$

for all $\varphi \in C^1([0, T] \times \bar{\Omega})$

Entropy inequality

$$\left[\int_{\Omega} \varrho s \varphi \, dx \right]_{t=0}^{t=\tau} \geq \int_0^{\tau} \int_{\Omega} [\varrho s \partial_t \varphi + \mathbf{s} \mathbf{m} \cdot \nabla_x \varphi] \, dx dt$$

for all $\varphi \in C^1([0, T] \times \bar{\Omega})$, $\varphi \geq 0$

Infinitely many weak solutions

Initial data

$$\varrho(0, \cdot) = \varrho_0, \mathbf{u}(0, \cdot) = \mathbf{u}_0, \vartheta(0, \cdot) = \vartheta_0.$$

Existence via convex integration

Let $N = 2, 3$. Let ϱ_0, ϑ_0 be piecewise constant (arbitrary) positive. Then there exists $\mathbf{u}_0 \in L^\infty$ such that the Euler system admits infinitely many admissible weak solutions in $(0, T) \times \Omega$.

Dissipative measure-valued (DMV) solutions

Parameterized measure

$$\underbrace{\mathcal{F}}_{\text{phase space}} = \left\{ \varrho \geq 0, \mathbf{m} \in R^3, E \in [0, \infty) \right\}, \quad \underbrace{Q_T}_{\text{physical space}} = (0, T) \times \Omega$$
$$\{\mathcal{V}_{t,x}\}_{(t,x) \in Q_T}, Y_{t,x} \in \mathcal{P}(\mathcal{F})$$

Field equations

$$\partial_t \langle \mathcal{V}_{t,x}; \varrho \rangle + \operatorname{div}_x \langle \mathcal{V}_{t,x}; \mathbf{m} \rangle = 0$$

$$\partial_t \langle \mathcal{V}_{t,x}; \mathbf{m} \rangle + \operatorname{div}_x \left\langle \mathcal{V}_{t,x}; \frac{\mathbf{m} \otimes \mathbf{m}}{\varrho} \right\rangle + \nabla_x \langle \mathcal{V}_{t,x}; p \rangle = D_x \mu_C$$

$$\partial_t \int_{\Omega} \langle \mathcal{V}_{t,x}; E \rangle dx + \mathcal{D} = 0, \quad \partial_t \langle \mathcal{V}_{t,x}; \varrho s \rangle + \operatorname{div}_x \langle \mathcal{V}_{t,x}; \mathbf{s} \mathbf{m} \rangle \geq 0$$

Compatibility

$$\int_0^T \int_{\Omega} |\mu_C| dx dt \leq C \int_0^T \mathcal{D} dt$$

Why to go measure-valued?

Motto: The larger (class) the better

- Universal limits of `numerical` schemes
- Limits of more complex physical systems - vanishing viscosity/heat conductivity limit
- Singular limits (low Mach etc.)

Weak-strong uniqueness

A (DMV) solution coincides with a smooth solution with the same initial data as long as the latter solution exists

Thermodynamic stability

Thermodynamic stability in the standard variables

$$\frac{\partial p(\varrho, \vartheta)}{\partial \varrho} > 0, \quad \frac{\partial e(\varrho, \vartheta)}{\partial \vartheta} > 0$$

Thermodynamic stability in the conservative variables

$$(\varrho, \mathbf{m}, E) \mapsto \varrho s(\varrho, \mathbf{m}, E)$$

is a (strictly) concave function

Thermodynamic stability in the polytropic case

$$\varrho s = \varrho S \left(\frac{p}{\varrho^\gamma} \right), \quad p = (\gamma - 1)\varrho e$$

$$S'(Z) > 0, \quad (1 - \gamma)S'(Z) - \gamma S''(Z)Z > 0$$

Relative energy

Relative energy in the standard variables

$$\begin{aligned}\mathcal{E}(\varrho, \vartheta, \mathbf{u} \mid \tilde{\varrho}, \tilde{\vartheta}, \tilde{\mathbf{u}}) \\ &= \frac{1}{2} \varrho |\mathbf{u} - \tilde{\mathbf{u}}|^2 + \partial_{\varrho} H_{\tilde{\vartheta}}(\tilde{\varrho}, \tilde{\vartheta})(\varrho - \tilde{\varrho}) - H_{\tilde{\vartheta}}(\tilde{\varrho}, \tilde{\vartheta}) \\ H_{\tilde{\vartheta}}(\varrho, \vartheta) &= \varrho \left(e(\varrho, \vartheta) - \tilde{\vartheta} s(\varrho, \vartheta) \right)\end{aligned}$$

Relative energy in the conservative variables

$$\begin{aligned}\mathcal{E}(\varrho, \mathbf{m}, E \mid \tilde{\varrho}, \tilde{\mathbf{m}}, \tilde{E}) \\ &= -\tilde{\vartheta} \left[\varrho s - \partial_{\varrho}(\varrho s)(\varrho - \tilde{\varrho}) - \nabla_{\mathbf{m}}(\varrho s) \cdot (\mathbf{m} - \tilde{\mathbf{m}}) - \partial_E(\varrho s)(E - \tilde{E}) \right. \\ &\quad \left. - \tilde{\varrho} \tilde{s} \right]\end{aligned}$$

Relative energy inequality

Relative energy revisited

$$\begin{aligned} \mathcal{E} \left(\varrho, \mathbf{m}, E \mid \tilde{\varrho}, \tilde{\vartheta}, \tilde{\mathbf{u}} \right) &\equiv E - \tilde{\vartheta} S(\varrho, \mathbf{m}, E) - \mathbf{m} \cdot \tilde{\mathbf{u}} + \frac{1}{2} \varrho |\tilde{\mathbf{u}}|^2 + p(\tilde{\varrho}, \tilde{\vartheta}) \\ &- \left(e(\tilde{\varrho}, \tilde{\vartheta}) - \tilde{\vartheta} s(\tilde{\varrho}, \tilde{\vartheta}) + \frac{p(\tilde{\varrho}, \tilde{\vartheta})}{\tilde{\varrho}} \right) \varrho \end{aligned}$$

Relative energy inequality

$$\left[\int_{\Omega} \left\langle \mathcal{V}_{t,x}; \mathcal{E} \left(\varrho, \mathbf{m}, E \mid \tilde{\varrho}, \tilde{\vartheta}, \tilde{\mathbf{u}} \right) \right\rangle dx \right]_{t=0}^{t=\tau} + \mathcal{D}(\tau) \leq \int_0^{\tau} \mathcal{R}(t) dt$$

Stability of strong solutions

Measure-valued strong uniqueness

Suppose the thermodynamic functions p , e , and s comply with the hypothesis of thermodynamic stability. Let (ϱ, \mathbf{m}, E) be a smooth (C^1) solution of the Euler system and let $(Y_{t,x}; \mathcal{D})$ be a dissipative measure-valued solution of the same system with the same initial data, meaning

$$Y_{0,x} = \delta_{\varrho_0(x), \mathbf{m}_0(x), E_0(x)} \text{ for a.a. } x \in \Omega.$$

Then

$$\mathcal{D} \equiv 0, \quad Y_{t,x} = \delta_{\varrho(t,x), \mathbf{m}(t,x), E(t,x)}$$

for a.a. $(t, x) \in (0, T) \times \Omega$.

Maximal dissipation principle

Entropy production rate

$$\partial_t(\varrho s) + \operatorname{div}_x(\varrho \mathbf{m}) = \boxed{\sigma} \geq 0$$

Dissipative ordering

$$\mathcal{V}_{t,x}^1 \succeq \mathcal{V}_{t,x}^2 \text{ iff } \sigma_1 \geq \sigma_2 \text{ in } [0, T) \times \Omega$$

$$\begin{aligned} & \int_0^T \int_{\Omega} \left[\left\langle \mathcal{V}_{t,x}^1; \mathcal{S}(\varrho, \mathbf{m}, E) \right\rangle \partial_t \varphi + \left\langle \mathcal{V}_{t,x}^1; \mathcal{S}(\varrho, \mathbf{m}, E) \frac{\mathbf{m}}{\varrho} \right\rangle \cdot \nabla_x \varphi \right] dx dt \\ & \leq \int_0^T \int_{\Omega} \left[\left\langle \mathcal{V}_{t,x}^2; \mathcal{S}(\varrho, \mathbf{m}, E) \right\rangle \partial_t \varphi + \left\langle \mathcal{V}_{t,x}^2; \mathcal{S}(\varrho, \mathbf{m}, E) \frac{\mathbf{m}}{\varrho} \right\rangle \cdot \nabla_x \varphi \right] dx dt \end{aligned}$$

Maximal dissipation principle

A (DMV) solution is admissible if it is *maximal* with respect to the ordering \succeq . A maximal (DMV) solution exists.

Generating MV solutions - zero viscosity limit

Navier–Stokes–Fourier system

$$\partial_t \varrho + \operatorname{div}_x(\varrho \mathbf{u}) = 0$$

$$\partial_t(\varrho \mathbf{u}) + \operatorname{div}_x(\varrho \mathbf{u} \otimes \mathbf{u}) + \nabla_x p = \varepsilon \operatorname{div}_x \mathbb{S}$$

$$\partial_t(\varrho e) + \operatorname{div}_x(\varrho e \mathbf{u}) + \varepsilon \nabla_x \mathbf{q} = \varepsilon \mathbb{S} : \nabla_x \mathbf{u} - p \operatorname{div}_x \mathbf{u}$$

Physical dissipation

$$\mathbb{S}(\vartheta, \nabla_x \mathbf{u}) = \mu(\vartheta) \left(\nabla_x \mathbf{u} + \nabla_x^t \mathbf{u} - \frac{2}{3} \operatorname{div}_x \mathbf{u} \mathbb{I} \right),$$

$$\mathbf{q} = -\kappa(\vartheta) \nabla_x \vartheta$$

Generating MV solutions - artificial viscosity

Lax–Friedrichs numerical scheme

$$\partial_t \varrho + \operatorname{div}_x(\varrho \mathbf{u}) = \varepsilon \operatorname{div}_x(\lambda \nabla_x \varrho)$$

$$\partial_t(\varrho \mathbf{u}) + \operatorname{div}_x(\varrho \mathbf{u} \otimes \mathbf{u}) + \nabla_x p = \varepsilon \operatorname{div}_x(\lambda \nabla_x(\varrho \mathbf{u}))$$

$$\partial_t E + \operatorname{div}_x((E + p)\mathbf{u}) = \varepsilon \operatorname{div}_x(\lambda \nabla_x E)$$

Entropy preserving

$$\partial(\varrho S) + \operatorname{div}_x(\varrho S \mathbf{u}) \boxed{\geq} \varepsilon \operatorname{div}_x(\lambda \varrho \nabla_x S) + \text{"defect"}$$

Brenner's model

Two velocities principle

$$\mathbf{u} - \mathbf{u}_m = \varepsilon K \nabla_x \log(\varrho)$$

Field equations

$$\partial_t \varrho + \operatorname{div}_x(\varrho \mathbf{u}_m) = 0$$

$$\partial_t(\varrho \mathbf{u}) + \operatorname{div}_x(\varrho \mathbf{u} \otimes \mathbf{u}_m) + \nabla_x p(\varrho, \vartheta) = \varepsilon \operatorname{div}_x \mathbb{S}$$

$$\begin{aligned} \partial_t \left(\varrho \left(\frac{1}{2} |\mathbf{u}|^2 + e(\varrho, \vartheta) \right) \right) + \operatorname{div}_x \left(\varrho \left(\frac{1}{2} |\mathbf{u}|^2 + e(\varrho, \vartheta) \right) \mathbf{u}_m \right) + \operatorname{div}_x(p(\varrho, \vartheta) \mathbf{u}) \\ + \varepsilon \operatorname{div}_x \mathbf{q} = \varepsilon \operatorname{div}_x(\mathbb{S} \mathbf{u}) \end{aligned}$$

Constitutive relations

$$\mathbb{S} = \mu \left(\nabla_x \mathbf{u} + \nabla_x^t \mathbf{u} - \frac{2}{3} \operatorname{div}_x \mathbf{u} \right), \quad \mathbf{q} = -\kappa \nabla_x \vartheta,$$

$$K = \frac{\kappa}{c_v \varrho}$$